

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** **EnergyGuard DCC Cabinet Casing**
According the DCC technology!
- **Article number:** DCC170HS-A
- **Application of the substance / the preparation** Paint
- **Manufacturer/Supplier:**
Monopoly B. V.
Lassusstraat 9A
1075 GV Amsterdam
The Netherlands
Tel: (+31)-20-679-10-27
info@energyguardcorp.com
- **Further information obtainable from:** Product Safety Department
- **Information in case of emergency:** Tel: (+31)-20-679-10-27

2 Hazards identification

- **Hazard description:**



Xn Harmful

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20/21 Harmful by inhalation and in contact with skin.

Restricted to professional users.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- **GHS label elements**



Warning

H226 - Flammable liquid and vapour.



Warning

H312 - Harmful in contact with skin.

H332 - Harmful if inhaled.

- **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

- **Response:**

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

(Contd. on page 2)

Trade name: EnergyGuard DCC Cabinet Casing
According the DCC technology!

(Contd. of page 1)

- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
 P322 Specific measures (see on this label).
 P363 Wash contaminated clothing before reuse.
 P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

• **Storage:**

P403+P235 Store in a well-ventilated place. Keep cool.

• **Disposal:**

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

• **Chemical characterization**

• **Description:** Mixture of substances listed below with nonhazardous additions.

• **Dangerous components:**

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9	xylene ☒ Xn, ☒ Xi; R 10-20/21-38 Warning: ⚠ 2.6/3; ⚠ 3.1.D/4, 3.1.I/4, 3.2/2	10-15%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7	2-methoxy-1-methylethyl acetate ☒ Xi; R 10-36 Warning: ⚠ 2.6/3; ⚠ 3.3/2	5-7%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4	ethylbenzene ☒ Xn, ☒ F; R 11-20 Danger: ⚠ 2.6/2 Warning: ⚠ 3.1.I/4	3-5%
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1	n-butyl acetate R 10-66-67 Warning: ⚠ 2.6/3; ⚠ 3.8/3	1-2,5%
CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356-00-4	Solvent naphtha (petroleum), light arom. ☒ Xn, ☒ Xi, ☒ N; R 37/38-51/53-65-67 Danger: ⚠ 3.10/1 Warning: ⚠ 3.2/2, 3.8/3 ⚠ 4.1.C/2	.15-0,25%
CAS: 64742-49-0 EINECS: 265-151-9 Index number: 649-328-00-1	Naphtha (petroleum), hydrotreated light Carc. Cat. 2, Muta. Cat. 2; ☒ Xn, ☒ Xi, ☒ F, ☒ N; R 11-38-51/53-65-67 Danger: ⚠ 3.6/1B, 3.10/1	.15-0,25%
CAS: 64742-82-1 EINECS: 265-185-4 Index number: 649-330-00-2	Naphtha (petroleum), hydrodesulfurized heavy ☒ Xn, ☒ N; R 10-51/53-65-66-67 Danger: ⚠ 3.6/1B, 3.10/1	.15-0,25%

• **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

• **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• **After skin contact:** Generally the product does not irritate the skin.

• **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Trade name: EnergyGuard DCC Cabinet Casing
According the DCC technology!

(Contd. of page 2)

- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene

IOELV	Short-term value: 442 mg/m ³ , 100 ppm Long-term value: 221 mg/m ³ , 50 ppm Skin
-------	--

108-65-6 2-methoxy-1-methylethyl acetate

IOELV	Short-term value: 550 mg/m ³ , 100 ppm Long-term value: 275 mg/m ³ , 50 ppm Skin
-------	--

100-41-4 ethylbenzene

IOELV	Short-term value: 884 mg/m ³ , 200 ppm Long-term value: 442 mg/m ³ , 100 ppm Skin
-------	---

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.

(Contd. on page 4)

Trade name: EnergyGuard DCC Cabinet Casing
According the DCC technology!

(Contd. of page 3)

Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form: Fluid
Colour: According to product specification
Odour: Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 137°C

· **Flash point:** 30°C

· **Ignition temperature:** 315°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1,1 Vol %
Upper: 7,0 Vol %

· **Vapour pressure at 20°C:** 6,7 hPa

· **Density at 20°C:** 1,304 g/cm³

· **Solubility in / Miscibility with water:**

Not miscible or difficult to mix.

(Contd. on page 5)

Trade name: EnergyGuard DCC Cabinet Casing
According the DCC technology!

(Contd. of page 4)

- **Viscosity:**
Kinematic at 20°C: 100 s (ISO 6 mm)
- **Solvent content:**
Organic solvents: 23,8 %
- **Solids content:** 76,1 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

1330-20-7 xylene

Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful

12 Ecological information

- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- **Product:**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**
- **ADR/RID class:** -

(Contd. on page 6)

Trade name: EnergyGuard DCC Cabinet Casing
According the DCC technology!

(Contd. of page 5)

- **Maritime transport IMDG:**
- **IMDG Class:** -
- **Marine pollutant:** No

- **Air transport ICAO-TI and IATA-DGR:**



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1263
- **Label** 3
- **Packaging group:** III
- **Proper shipping name:** PAINT

- **UN "Model Regulation":** -

15 Regulatory information

- **Labelling according to EU guidelines:**
- **Code letter and hazard designation of product:**



Xn Harmful

- **Hazard-determining components of labelling:**
xylene
- **Risk phrases:**
10 Flammable.
20/21 Harmful by inhalation and in contact with skin.
- **Safety phrases:**
23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
36/37 Wear suitable protective clothing and gloves.
51 Use only in well-ventilated areas.
60 This material and its container must be disposed of as hazardous waste.
- **Special labelling of certain preparations:**
Restricted to professional users.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**
10 Flammable.
11 Highly flammable.
20 Harmful by inhalation.
20/21 Harmful by inhalation and in contact with skin.
36 Irritating to eyes.
37/38 Irritating to respiratory system and skin.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.
66 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 7)

Trade name: EnergyGuard DCC Cabinet Casing
According the DCC technology!

(Contd. of page 6)

67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** product safety department

· **Contact:** Tel: (+31)-20-679-10-27

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent