Safety Data Sheet according to 1907/2006/EC, Article 31





efficiency coatings for hvac & r equipment

Revision: 20.07.2009

Page 1/8

1 Identification of the substance/preparation and of the company/undertaking

- · Product details
- Trade name: <u>EnergyGuard DCC Green</u> <u>According the DCC technology!</u>
- · Article number: DCC218-3
- · Application of the substance / the preparation Paint

• Manufacturer/Supplier: Monopoly B.V. Lassusstraat 9A 1075 GV Amsterdam The Netherlands Tel: (+31)-20-679-10-27 info@energyguardcorp.com

· Further information obtainable from: Product Safety Department

· Information in case of emergency: Tel: (+31)-20-679-10-27

2 Hazards identification

· Hazard description:



N Dangerous for the environment

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

R 10 Flammable.

R 20 Harmful by inhalation.

R 36/37/38 Irritating to eyes, respiratory system and skin.

- R 40 Limited evidence of a carcinogenic effect.
- R 42/43 May cause sensitisation by inhalation and skin contact.
- R 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains isocyanates. See information supplied by the manufacturer

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

GHS label elements



- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

> Warning

H226 - Flammable liquid and vapour.

Warning

H410 - Very toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Safety Data Sheet according to 1907/2006/EC, Article 31



efficiency coatings for hvac & r equipment

Revision: 20.07.2009

Printing date 20.07.2009

Trade name: EnergyGuard DCC Green According the DCC technology!

(Contd. of page 1) Warning H332+EUH070 - Harmful if inhaled. Toxic by eye contact. H335 - May cause respiratory irritation. Contains isocyanates. May produce an allergic reaction. · Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting/equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P261 Avoid breathing dust/fume/gas/mist/vapours/spray. P264 Wash thoroughly after handling. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/protective clothing/eye protection/face protection. P281 Use personal protective equipment as required. P285 In case of inadequate ventilation wear respiratory protection. · Response: P302+P352 IF ON SKIN: Wash with plenty of soap and water. P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. P308+P313 IF exposed or concerned: Get medical advice/attention. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P314 Get medical advice/attention if you feel unwell. P321 Specific treatment (see on this label). P332+P313 If skin irritation occurs: Get medical advice/attention. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. P362 Take off contaminated clothing and wash before reuse. P363 Wash contaminated clothing before reuse. P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P391 Collect spillage. Storage: P403+P233 Store in a well-ventilated place. Keep container tightly closed. P403+P235 Store in a well-ventilated place. Keep cool. P405 Store locked up. · Disposal: P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Chemical characterization

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

Page 2/8



efficiency coatings for hvac & r equipment

Revision: 20.07.2009

Page 3/8

Printing date 20.07.2009

Trade name: EnergyGuard DCC Green According the DCC technology!

| | | (Contd. of page |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| Dangerous compo | nents: | |
| CAS: 98-56-6 EINECS: 202-681-1 | 4-chloro-alpha,alpha,alpha-trifluorotoluene Xi; R 10-36/38 Warning: ∲ 2.6/3; ∲ 3.2/2, 3.3/2 | 25-50% |
| CAS: 9016-87-9 | diphenylmethanediisocyanate,isomeres and homologues Carc. Cat. 3; X Xn, Xi; R 20-36/37/38-40-42/43-48/20 Danger: 3.4.R/1, 3.2/2, 3.3/2, 3.4.S/1 Warning: 1.1.I/4, 3.8/3 | |
| CAS: 137-30-4 EINECS: 205-288-3 | ziram (ISO) T+, Xi, N; R 22-26-37-41-43-48/22-50/53 Danger: 3.1.1/2, 3.1.0/4, 3.4.S/1, 3.8/3; 3.3/1 Warning: 4 3.9/2; 4 4.1.C/1 | 0.5-1% |

• Additional information: For the wording of the listed risk phrases refer to section

4 First aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
 Measures for environmental protection:

Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

 Measures for cleaning/collecting: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- Information for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke.

(Contd. on page 4)



Revision: 20.07.2009

Printing date 20.07.2009

Trade name: EnergyGuard DCC Green According the DCC technology!

Protect against electrostatic charges.

- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO

· Additional information: The lists valid during the making were used as basis.

· Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

Form:

Fluid

(Contd. on page 5)

(Contd. of page 3)

Page 4/8



efficiency coatings for hvac & r equipment

Revision: 20.07.2009

Page 5/8

Printing date 20.07.2009

Trade name: EnergyGuard DCC Green According the DCC technology!

| | (Contd. of page 4) | |
|-----------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|--|
| Colour: Odour: | According to product specification Characteristic | |
| Change in condition Melting point/Melting range: Boiling point/Boiling range: | | |
| · Flash point: | 39°C | |
| · Ignition temperature: | 400°C | |
| · Self-igniting: | Product is not selfigniting. | |
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. | |
| · Density at 20°C: | 1.3586 g/cm ³ | |
| Solubility in / Miscibility with water: | y with Not miscible or difficult to mix. | |
| Viscosity: Kinematic at 20°C: | 20 s (ISO 6 mm) | |
| Solvent content: Organic solvents: | 36.5 % | |
| · Solids content: | 56.2 % | |

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Dangerous reactions No dangerous reactions known.

· Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values relevant for classification:

137-30-4 ziram (ISO)

Oral LD50 1400 mg/kg (rat)

· Primary irritant effect:

- · on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

· Sensitisation May cause sensitisation by inhalation and skin contact.

12 Ecological information

· Ecotoxical effects:

· Remark: Very toxic for fish

(Contd. on page 6)

Safety Data Sheet according to 1907/2006/EC, Article 31



efficiency coatings for hvac & r equipment

Revision: 20.07.2009

Printing date 20.07.2009

Trade name: EnergyGuard DCC Green According the DCC technology!

(Contd. of page 5)

Page 6/8

 General notes: Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms

13 Disposal considerations

· Product:

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

| 14 Transport informa | ation | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------|-----------------|--|
| · Land transport ADR/RID (cross-border) | | | |
| | | | |
| ADR/RID class: Danger code (Kemler UN-Number: Packaging group: Hazard label: Special marking: | 3 Flammable liquids.): 30 1263 III 3 Symbol (fish and tree) | | |
| Description of goods Maritime transport IN | : 1263 PAINT | | |
| | | | |
| IMDG Class: UN Number: Label Packaging group: EMS Number: Marine pollutant: Proper shipping nam | 3 1263 3 III F-E,S-E No e : PAINT | | |
| · Air transport ICAO-T | and IATA-DGR: | | |
| ICAO/IATA Class: UN/ID Number: Label Packaging group: Proper shipping name | 3 1263 3 III e: PAINT | | |
| | n": UN1263, PAINT, 3, III | (Contd. on page | |

- GB

ENERGY GUARD efficiency coatings for hvac & r equipment

Revision: 20.07.2009

Printing date 20.07.2009

Trade name: EnergyGuard DCC Green According the DCC technology!

· Environmental hazards: Environmentally hazardous substance, liquid; Marine Pollutant

(Contd. of page 6)

Page 7/8

15 Regulatory information

- · Labelling according to EU guidelines:
- \cdot Code letter and hazard designation of product:



Xn Harmful N Dangerous for the environment

- *Hazard-determining components of labelling:* diphenylmethanediisocyanate,isomeres and homologues ziram (ISO)
- · Risk phrases:
- 10 Flammable.
- 20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

- 40 Limited evidence of a carcinogenic effect.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

23 Do not breathe aerosol.

36/37 Wear suitable protective clothing and gloves.

- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 51 Use only in well-ventilated areas.
- 57 Use appropriate container to avoid environmental contamination.
- · Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant R-phrases

- 10 Flammable.
- 20 Harmful by inhalation.
- 22 Harmful if swallowed.
- 26 Very toxic by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

- 36/38 Irritating to eyes and skin.
- 37 Irritating to respiratory system.
- 40 Limited evidence of a carcinogenic effect.
- 41 Risk of serious damage to eyes.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 43 May cause sensitisation by skin contact.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.
- 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Department issuing MSDS: product safety department

· Contact: Tel: (+31)-20-679-10-27

(Contd. on page 8)

GB

Safety Data Sheet according to 1907/2006/EC, Article 31



efficiency coatings for hvac & r equipment

Revision: 20.07.2009

Printing date 20.07.2009

Trade name: EnergyGuard DCC Green According the DCC technology!

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA) ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. of page 7)

GB

Page 8/8