Safety Data Sheet according to 1907/2006/EC, Article 31





efficiency coatings for hvac & r equipment

Revision: 29.09.2009

Page 1/5

1 Identification of the substance/preparation and of the company/undertaking

- Product details
- · Trade name: EnergyGuard DCC SF PART B
- · Article number: DCCSFB
- · Application of the substance / the preparation Paint

• Manufacturer/Supplier: Monopoly B.V. Lassusstraat 9A 1075 GV Amsterdam The Netherlands Tel: (+31)-20-679-10-27 info@energyguardcorp.com

- Further information obtainable from: Product Safety Department
- Information in case of emergency: Tel: (+31)-20-679-10-27

2 Hazards identification

· Hazard description:



Carc. Cat. 3 Xn Harmful

· Information concerning particular hazards for human and environment:

R 20 Harmful by inhalation.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 40 Limited evidence of a carcinogenic effect.

- R 42/43 May cause sensitisation by inhalation and skin contact.
- R 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Contains isocyanates. See information supplied by the manufacturer

GHS label elements



H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

Warning

H332 - Harmful if inhaled. H335 - May cause respiratory irritation.

Contains isocyanates. May produce an allergic reaction.

· Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P285 In case of inadequate ventilation wear respiratory protection.

(Contd. on page 2)

Printing date 29.09.2009



efficiency coatings for hvac & r equipment

Revision: 29.09.2009

Page 2/5

Trade name: EnergyGuard DCC SF PART B

	(Contd. of page 1)
· Response:	
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P33	8 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362	Take off contaminated clothing and wash before reuse.
P363	Wash contaminated clothing before reuse.
· Storage:	Ŭ
	e in a well-ventilated place. Keep container tightly closed.
	e locked up.
· Disposal:	
	contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

· Chemical characterization:

- · CAS No. Description
- 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues
- · Identification number(s) n.v.t.

4 First aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

· Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Person-related safety precautions: Not required.
- · Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- *Measures for cleaning/collecting:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

(Contd. on page 3)

ENERGY GUARD

efficiency coatings for hvac & r equipment

Revision: 29.09.2009

Printing date 29.09.2009

Trade name: EnergyGuard DCC SF PART B

(Contd. of page 2)

Page 3/5

Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- Information for safe handling: Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Prevent iormation of aerosols.
- Information about fire and explosion protection: No special measures required.
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

· Ingredients with limit values that require monitoring at the workplace:

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO

· Additional information: The lists valid during the making were used as basis.

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection:



Tightly sealed goggles

(Contd. on page 4)

GB

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 29.09.2009

Trade name: EnergyGuard DCC SF PART B

Revision: 29.09.2009

(Contd. of page 3)

General Information		
Form:	Fluid	
Colour:	Colourless	
Odour:	Characteristic	
Change in condition		
Melting point/Melting rang		
Boiling point/Boiling range	e: 190°C	
Flash point:	111°C	
Ignition temperature:	400°C	
Danger of explosion:	Product does not present an explosion hazard.	
່ Vapour pressure at 25℃:	0.0002 hPa	
Density at 20°C:	1.24 g/cm³	
Solubility in / Miscibility with	h	
water:	Not miscible or difficult to mix.	
Organic solvents:	0.0 %	
Solids content:	100.0 %	

ENERGY

efficiency coatings for hvac & r equipment

JUAR

10 Stability and reactivity

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- · Dangerous reactions No dangerous reactions known.
- · Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through inhalation. Sensitization possible through skin contact.
- · Sensitisation May cause sensitisation by inhalation and skin contact.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- Carc. Cat. 3

12 Ecological information

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- · Product:
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 5)

Safety Data Sheet according to 1907/2006/EC, Article 31



efficiency coatings for hvac & r equipment

Revision: 29.09.2009

Printing date 29.09.2009

Trade name: EnergyGuard DCC SF PART B

(Contd. of page 4)

Page 5/5

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · Land transport ADR/RID (cross-border)
- ADR/RID class:
- · Maritime transport IMDG:
- · IMDG Class:
- · Marine pollutant: No
- · Air transport ICAO-TI and IATA-DGR:
- · ICAO/IATA Class: -
- · UN "Model Regulation": -

15 Regulatory information

- · Labelling according to EU guidelines:
- · Code letter and hazard designation of product:



Carc. Cat. 3 Xn Harmful

· Risk phrases:

20 Harmful by inhalation.

36/37/38 Irritating to eyes, respiratory system and skin.

- 40 Limited evidence of a carcinogenic effect.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- · Safety phrases:
- 1/2 Keep locked up and out of the reach of children.
- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 36/37 Wear suitable protective clothing and gloves.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

 Special labelling of certain preparations: Contains isocyanates. See information supplied by the manufacturer

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: product safety department
- · Contact: Tel: (+31)-20-679-10-27
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)