

1 Identification

- **Product identifier**
- **Trade name:** EnergyGuard DCC Aluminum
- **Article number:** DCC218ALU
- **Application of the substance / the mixture** Paint
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Monopoly B.V.
p/a Gaffelveld 3
3993 RC Houten
The Netherlands

- info@energyguardcorp.com
- **Information department:**
Product Safety Department
R&D department
- **Emergency telephone number:** 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Aromatisch polyisocyanat-prepolymeer
diphenylmethanediisocyanat, isomeres and homologues
ethylbenzene
Prepolymer based on aromatic polyisocyanate

Trade name: EnergyGuard DCC Aluminum

(Contd. of page 1)

4,4'-methylenediphenyl diisocyanate
o-(p-isocyanatobenzyl)phenyl isocyanate
4-isocyanatosulphonyltoluene

Hazard statements

Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of causing cancer.
May cause respiratory irritation.
May cause damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.
[In case of inadequate ventilation] wear respiratory protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Specific treatment (see on this label).
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If experiencing respiratory symptoms: Call a poison center/doctor.
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

Classification system:

NFPA ratings (scale 0 - 4)



HMIS-ratings (scale 0 - 4)



Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

(Contd. on page 3)

Trade name: **EnergyGuard DCC Aluminum**

(Contd. of page 2)

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization:** Mixtures

· **Description:** Resin mixture

· **Dangerous components:**

CAS: 1330-20-7	xylene	15-<20%
CAS: 67815-87-6	Aromatisch polyisocyanat-prepolymeer	15-<20%
CAS: 7429-90-5	aluminium powder (stabilised)	10-<15%
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	7-<10%
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	7-<10%
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	7-<10%
CAS: 64742-48-9	Naphtha (petroleum), hydrotreated heavy	7-<10%
CAS: 127821-00-5	Prepolymer based on aromatic polyisocyanate	7-<10%
CAS: 100-41-4	ethylbenzene	3-<5%
CAS: 123-86-4	n-butyl acetate	1-<2.5%
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	1-<2.5%
CAS: 5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	1-<2.5%
CAS: 4083-64-1	4-isocyanatosulphonyltoluene	0.5-<1%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

· **Protective equipment:**

No special measures required.

(Contd. on page 4)

Trade name: EnergyGuard DCC Aluminum

(Contd. of page 3)

Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 1330-20-7	xylene	130 ppm
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	0.15 mg/m ³
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	50 ppm
CAS: 100-41-4	ethylbenzene	33 ppm
CAS: 123-86-4	n-butyl acetate	5 ppm
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m ³
CAS: 70657-70-4	2-methoxypropyl acetate	50 ppm
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate	0.020 ppm

· **PAC-2:**

CAS: 1330-20-7	xylene	920* ppm
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3.6 mg/m ³
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	1,000 ppm
CAS: 100-41-4	ethylbenzene	1100* ppm
CAS: 123-86-4	n-butyl acetate	200 ppm
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m ³
CAS: 70657-70-4	2-methoxypropyl acetate	1,000 ppm
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate	0.083 ppm

· **PAC-3:**

CAS: 1330-20-7	xylene	2500* ppm
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	22 mg/m ³
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5000* ppm
CAS: 100-41-4	ethylbenzene	1800* ppm
CAS: 123-86-4	n-butyl acetate	3000* ppm
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
CAS: 70657-70-4	2-methoxypropyl acetate	5,000 ppm
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate	0.51 ppm

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 5)

Trade name: EnergyGuard DCC Aluminum

(Contd. of page 4)

- No special measures required.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

CAS: 1330-20-7 xylene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: (150) ppm Long-term value: (100) NIC-20 ppm BEI, A4

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

WEEL	Long-term value: 50 ppm
------	-------------------------

CAS: 100-41-4 ethylbenzene

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 20 NIC-20 ppm BEI, A3, NIC: OTO, BEI, A3

CAS: 123-86-4 n-butyl acetate

PEL	Long-term value: 710 mg/m ³ , 150 ppm
REL	Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm
TLV	Short-term value: 150 ppm Long-term value: 50 ppm

CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate

PEL	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV	Long-term value: 0.005 ppm

- **Ingredients with biological limit values:**

CAS: 1330-20-7 xylene

BEI	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----	--

(Contd. on page 6)

Trade name: EnergyGuard DCC Aluminum

(Contd. of page 5)

CAS: 100-41-4 ethylbenzene

BEI 0.15 g/g creatinine
 Medium: urine
 Time: end of shift at end of workweek
 Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
 Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the eyes and skin.
- **Breathing equipment:**
 In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
 The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
 The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid
Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Mixture is non-polar/aprotic.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 137-143 °C (278.6-289.4 °F)

· **Flash point:** 30 °C (86 °F)

(Contd. on page 7)

Trade name: **EnergyGuard DCC Aluminum**

(Contd. of page 6)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	240 °C (464 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapor pressure at 20 °C (68 °F):	6.7-8.2 hPa (5-6.2 mm Hg)
· Density at 20 °C (68 °F):	1.078 g/cm ³ (8.99591 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C (68 °F):	15 s (ISO 6 mm)
· Solvent content:	
Organic solvents:	46.0 %
VOC content:	46.00 %
	495.9 g/l / 4.14 lb/gal
Solids content:	54.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

CAS: 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

CAS: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

Inhalative	LC50/4 h	>15 mg/l (rat)
------------	----------	----------------

(Contd. on page 8)

Trade name: EnergyGuard DCC Aluminum

(Contd. of page 7)

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)
CAS: 101-68-8 4,4'-methylenediphenyl diisocyanate		
Oral	LD50	2,200 mg/kg (mouse)
Inhalative	LC50/4 h	>15 mg/l (rat)
CAS: 5873-54-1 o-(p-isocyanatobenzyl)phenyl isocyanate		
Oral	LD50	2,000 mg/kg (rat)
		mg/kg (rabbit)
Dermal	LD50	9,400 mg/kg (rabbit)
CAS: 4083-64-1 4-isocyanatosulphonyltoluene		
Oral	LD50	2.234 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

· **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
CAS: 1330-20-7	xylene	3
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	3
CAS: 100-41-4	ethylbenzene	2B
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	3

· **NTP (National Toxicology Program)**

CAS: 584-84-9	4-methyl-m-phenylene diisocyanate	R
---------------	-----------------------------------	---

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.

(Contd. on page 9)

Trade name: EnergyGuard DCC Aluminum



(Contd. of page 8)

- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR/RID/ADN, ADN, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR/RID/ADN, ADN** 1263 PAINT
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR/RID/ADN, IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADN**
- **ADN/R Class:** 3 Flammable liquids
- **Packing group**
- **DOT, ADR/RID/ADN, IMDG, IATA** III
- **Environmental hazards:** Not applicable.
- **Special precautions for user** Warning: Flammable liquids
- **Hazard identification number (Kemler code):** 30
- **EMS Number:** F-E, S-E
- **Stowage Category** A
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 10)

Trade name: EnergyGuard DCC Aluminum

(Contd. of page 9)

· Transport/Additional information:	
· ADR/RID/ADN	
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture
No further relevant information available.

· Sara

· Section 355 (extremely hazardous substances):

CAS: 584-84-9	4-methyl-m-phenylene diisocyanate
---------------	-----------------------------------

· Section 313 (Specific toxic chemical listings):

CAS: 1330-20-7	xylene
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues
CAS: 100-41-4	ethylbenzene
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate

· TSCA (Toxic Substances Control Act):

CAS: 1330-20-7	xylene	ACTIVE
CAS: 67815-87-6	Aromatisch polyisocyanat-prepolymeer	ACTIVE
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	ACTIVE
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	ACTIVE
CAS: 127821-00-5	Prepolymer based on aromatic polyisocyanate	ACTIVE
CAS: 100-41-4	ethylbenzene	ACTIVE
CAS: 123-86-4	n-butyl acetate	ACTIVE
CAS: 68611-44-9	Kieselsäure hydrophobiert hochdisperse	ACTIVE
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	ACTIVE
CAS: 5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	ACTIVE
CAS: 122-51-0	triethyl orthoformate	ACTIVE
CAS: 4083-64-1	4-isocyanatosulphonyltoluene	ACTIVE
CAS: 2536-05-2	2,2'-methylenediphenyl diisocyanate	ACTIVE
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate	ACTIVE

· Hazardous Air Pollutants

CAS: 1330-20-7	xylene
CAS: 100-41-4	ethylbenzene
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate

· Proposition 65

· Chemicals known to cause cancer:

CAS: 100-41-4	ethylbenzene
---------------	--------------

(Contd. on page 11)

Trade name: EnergyGuard DCC Aluminum

(Contd. of page 10)

· Chemicals known to cause reproductive toxicity for females:		
None of the ingredients is listed.		
· Chemicals known to cause reproductive toxicity for males:		
None of the ingredients is listed.		
· Chemicals known to cause developmental toxicity:		
None of the ingredients is listed.		
· Carcinogenicity categories		
· EPA (Environmental Protection Agency)		
CAS: 1330-20-7	xylene	I
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues	CBD
CAS: 100-41-4	ethylbenzene	D
CAS: 101-68-8	4,4'-methylenediphenyl diisocyanate	D, CBD
· TLV (Threshold Limit Value)		
CAS: 1330-20-7	xylene	A4
CAS: 100-41-4	ethylbenzene	A3
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate	(A4)
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
CAS: 584-84-9	4-methyl-m-phenylene diisocyanate	
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.		

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** product safety department

· **Contact:**

· **Date of preparation / last revision** 06/15/2022 / 2

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**